

Bush-Whacker HD-96

Read More

SKU:HD-96

Price:\$7800

Categories: Bush-Whacker

Product Description

Bush-Whacker HD-96

Gearboxes: 540(Standard) 120 HP main or transfer box 100 HP outboard boxes Gearboxes have forged alloy steel malleable housings, carburized and hardened gears and shafts, tapered and ball bearings.

Slip Clutch: Heavy-Duty clutch Spring type adjustment Four friction discs on main shaft Outboard protection by means of shock absorbing rubber elements connected to splined yokes which form a coupler.

Blades: $\frac{1}{2}$ " x 4" material Alloy spring steel Airlift design Free-swinging when encountering obstructions 4-inch overlap Blade tip speed: 15,480 FPM

Drive Shafts: Category 4 main input and side drives Category 4 80-degree constant velocity main drive shaft optional for pull model Shielded PTO's made from the finest quality propeller shaft material and needle bearing universal joins Wheels: Two solid rubber grooved tires standard Independent shock absorbing system for rear suspension Optional: aircraft tires or implement tires, dual axle arms (4 tires total).

Bush-Whacker Special Deck: 10-gauge skin ¼" sides Heavy duty T-frame design with one-piece electric welded frame Hydraulic Adjustments: Hydraulic cylinder controls cutting and traveling hei\ght adjustments for pull models Dimensions: Cutting Width: 96" Cutting Height: 2" to 12" Overall Width: 105" Overall Length: 91" Transportation width: 105"